TA AL 0 Ų, 01 10 N ş 100 FORE

PCT

(22) International Filing Date:

WORLD INTELLECTUAL PROPERTY ORGANIZATION

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7		(11) International Publication Number:	WO 00/56455
B01L	AZ	(43) Inturnational Publication Date: 28 Sentem	nhee 2000 (24 e9 00)

20 March 2000 (20.03.00)

PCT/GB00/01029 (21) International Application Number:

(30) Priority Data: 9906477.6 19 March 1999 (19,03.99) GB

(71) Applicant (for all designated States except US): PYROSE

QUENCING AB [SE/SE]: Vallongatan 1, S-752 28 Uppsala (SE).

(71) Applicant (for GB only): PIESOLD, Alexander, James (GB/GB); Frank B. Dehn & Co., 179 Queen Victoria Street, Published London EC4V 4EL (GB).

(72) Inventore and (75) Inventors/Applicants (for US only): HAGERLID, Peter [SE/SE]: Skoldungagatan 1, S-753 34 Uppsala (SE). EHRING, Hanno [DE/SE]: Karisrogatan 83a, S-752 39 Uppsala (SE). EKSTROM, Bjorn (SE/SE); Järpvägen 27, S-756 53 Uppsala (SE).

(74) Agent: SAMUELS, Adrian, J.; Frank B. Detin & Co., 179 Outen Victoria Street, London EC4V 4EL (GB).

(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FJ, GB, GD, GE, GH, GM, HR, HU, ID, IL. IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO potent (GH, GM. KE, LS, MW. SD. SL. SZ, TZ. UG, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT. BE. CH. CY, DE. DK, ES, FI, FR, GB. GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ. CF, CG, CL, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Without international search report and to be republished upon receipt of that report.

(54) Title: LIQUID DISPENSING APPARATUS

(57) Abstract

A liquid dispensing apparatus comprises a liquid reservoir (32), an outlet port (6: 36) and driving means for forcing liquid (4) through the outlet port (6; 36). The driving means generates a pulse of gas which impinges upon the liquid (4) in the reservoir (32) so as to force liquid (4) through the outlet part (6; 36). Also disclosed is a cassette comprising a plurality of cartridges for dispensing liquid therefrom. Each carridge comprises a liquid reservoir (32) and an outlet member (36) mounted so as to close an opening (34) in the liquid reservoir (32). The outlet member (36) provides an outlet port through which the liquid can be forced by a pulse of pressurised gas.

